# Some aspects improvement of industrial pipeline transport

N. Chernetskaya-Beletskaya, I. Baranov, M. Miroshnykova, S. Kravchenko, M. Bragin

Volodymyr Dahl East-Ukrainian National University, e-mail: <u>logistyka.snu.ua@gmail.ru</u>

Received January 5. 2017: accepted January 28. 2017

Summary. Improvement and development of new highly efficient energy-saving methods of pipeline transport is proposed to carry out on the basis of modern scientific approaches. The new concept and its implementation on the synergic basis are proposed. It is shown that stochastic modes of mixtures' flow arise at passing through intermittence, i.e. they are the result of collision of asymptotically stable and unstable motion states. There is presented graph of the dependence of energy of mixture volume on parameter  $\Pi$ , reflecting the extent of instability. In this graph, three areas are defined: in area I oscillatory motion of material particles takes place, without separation from the surface of the pipe, in area II particles are in an unstable state; in area III particles are in suspension (transportation mode is in flight). Analysis of areaII shows that individual particles of volume of moving mixture have properties to enter the intermitentmodeat a slow change in parameter  $\Pi$ .

**Key words:** pipeline transport, bulk material, synergy, intermittence, Energy saving.

#### **INTRODUCTION**

Scientific and technological progress, aimed at solving the most important problems facing the Ukrainian industries, primarily fuel, energy, metal, construction and environmental ones, is impossible without increase in efficiency of pneumatic and hydraulic industrial pipeline transport. Industrial enterprises widely use high-pressure pneumatic conveying systems with a number of disadvantages: high velocityof mixtures'flow in the pipeline, hence high energy consumption for transporting air-fuel mixtures; high wear of pipelines and ancillary equipment; degradation of particles of bulk materials; pipeline blockage; need to purify large volumes of air emitted into the environment; unstable sedimentation of material particles in the pipelinewhile using hydraulic transport.

In Ukraine, there is an acute problem of oil and gas shortage. An alternative to these energy sources is coal water fuel (CWF), obtained from finely ground coal of any brand, water and reagent-plasticizer. Use of CWF in industry has a number of advantages: CWF is relatively environmentally friendly source of energy, its combustion products contain much less soot, nitrogen and sulphur oxides; CWF is an economical type of fuel; it has sufficiently high calorific value and can reduce costs on its transportation through usage of pipeline transport. At the same time,hydrotransport systems design for CWF has some specific features that are not addressed sufficiently.

# ANALYSIS OF MAIN RESEARCHES AND PUBLICATIONS

The fundamental monograph by Loitsiansky L.G. [1] presents differential equations for dynamics of both homogeneous and heterogeneous media that have become the basis for further research and development in the field of pipeline transport.

The works of Smoldyrev A.E. [2,3] consider the laws of flow of bulk materials using pneumatic and hydraulic methods of transportation. The basis of this theory is separation of transported materials into classes. Then equations of flow of mixtures are considered and the main parameters of hydraulic and pneumatic conveying systems are determined for each class according to grain composition of mixtures.

Works [1, 4] describe the main aspects of mechanics of multiphase mediawith different structures (gas mixtures, bubbly liquids, gas and heat carriers of vapourliquid boilers), discuss methods for describing interfacial interaction in dispersive media. Works [1, 2] give the theory of sound, shock and kinematic waves and oscillatory motions in two-phase media. On the basis of methods and approaches outlined in sources [5,6] there is considered mechanicsof vibration and vibro-pneumatic conveying of bulk materials with regard to flow mode of individual particles aloft in suspension. The averaged energy balance equation of *i*-phase is proved and provided, taking into account the effect of surface, bulk, interfacial and internal forces of the given volume [6]. However, practical use of these approaches is unlikely feasible due to the need of using a lot of hardly determinable parameters.

Works [7, 8] consider the issues of fluidization of homogeneous media, as well as applied mechanics of heterogeneous media. Researches [9 - 11] describe the results of studies of various parameters of pneumatic conveying systems during turbulent flow, transportation of gas-material flow, velocity and pressure losses.

The work carried out studies that focus on the effect of silting of dams, which is caused by instability and sedimentation volatility of hydraulic fluids. Experiments by V.V. Traynis [12] with finely dispersed coal water suspensions showed that the nature of their flow is somewhat different from the flow of ideal viscoplastic fluid. Actual flow starts at lower shear stresses, it follows from the theory of viscoplastic flow. There was also found the phenomenon of spontaneous flow cessation at low velocity.

This issue is given a lot of attention in papers [13,14]. They present research of processes ofhydro transportationof highly concentrated suspensions at different shear stresses, transportation velocity and concentrations of the solid ingredient. In addition, much research is devoted to issues of sedimentation stability of suspensions, depending on various factors. It follows from the obtained data that the rational choice of concentration and particle size of the solid ingredient, and the choice of an adequate transportation mode determine effectiveness of the entire hydrotransport system [15,16].

#### OBJECTIVES

The aim of this work is to study the laws of flow of mixtures in fluidliftand their features referring to hydraulic and pneumatic transport, as well as development of physical and scientific bases of creation of new, highly efficient energy-saving methods of pipeline transport.

#### MAIN RESEARCH RESULTS

The modern approach to development of promising pipeline transportation methods [17-20] is based on the research of phase states and transitions of air-fuel and hydraulic mixtures, conditions of their formation and preservation of stability in different parts of the transport pipeline. Mixtures' flow is accompanied by complex processes, which are consequences of variety of combinations of phases and their structures, interfacial and intraphase interactions and transitions.

Since pneumatic and hydraulic transport transit solid material using the carrying flow (either gas or liquid) in the course of its operation, then with a certain degree of probability it can be argued that they comply with the fundamental laws of physics.

Studies in flow modes in pneumatic transport pipelineof homogeneous and heterogeneous media (gassolids) [17-20] have shown that transition from laminar to stable turbulent flow through a number of unstable intermediate states take place in the pipeline. Within one pipeline there may be two or more flow modeswith their mutual sequence of transitions. Pneumatic systems operating in wave and batch modes of flow of air-fuel mixtures, in addition to general incremental flow of bulk material along the pipeline transport, there take place inside wave and inside batch turbulence characterized by formation of a large number of vortices. At the same time characteristics of turbulent flow mode are kept, i.e., its disequilibrium, a large number of macroscopic degrees of freedom, significant and often decisive role of hydrodynamic fluctuations arising due to excitation of a large number of macroscopic degrees of freedom, its unpredictability to a great extent.

Transportation of bulk materials using transport pipeline under the influence of the carrying flow can be seen as an open system, which possesses unevenness associated with energy supply and resistance to movement, a large number of interacting subsystems of dynamic variables, viscosity and medium shear stress (its intrinsic properties), macroscopic interaction among particles and carryingflow. The peculiarity of this system is the phenomenon of intermittency, i.e. sequential change in regular and temporary time states of motion (the processes of formation and destruction of structures, transitions of laminar flow into the turbulent one and vice versa). Under certain conditions in pneumatic conveying pipeline there emerge ordered structures and forms of motion of the originally disordered, irregular forms of motion without special ordering external influences on the system [21-23].

Adoption of the basic postulates of synergy [21-24]: relative degree of state order in open systems, helping to distinguish the "order" from the "chaos"; criterion of the degree of chaos or order K - entropy (entropy of Krylov-Kolmogorov-Sinay), Lyapunov exponents, Boltzmann-Gibbs-Shannon entropy (H -Boltzmann's theorem ofthermal equilibrium, S-theorem); adoption of entropy differences as Lyapunov function, and adoption of the fact that the laminar flow accepted as a state of chaos is unstable; entropy production principle - the system is moving towards reducing entropy production; turbulent flow is more ordered than laminar flow; by the criterion of S-theorem transition from laminar flow to the turbulent one is a process of self-organization; establishing new macroscopic relations among individual areas and significant complication of the structure suggest that constantly occurringnonequilibrium phase transitions in pneumatic conveying pipeline are carried out according to  $O \leftrightarrow C$ (order  $\leftrightarrow$  chaos), i.e. under the scheme of selforganization[25].

State of local equilibrium in laminar flow is characterized by the following distribution [22]:

$$f_{\pi}(r,v) = \left(\frac{m}{2\pi kT}\right)^{3/2} \exp\left[-\frac{m(vV_{\pi}(r))^2}{2kT}\right], \quad (1)$$

where:  $V_{n}$  is an average velocity of laminar flow.

The derivative of the control parameter (Reynolds number is accepted as a control parameter) is:

$$\frac{d}{d\operatorname{Re}}(S_{\pi}-S_{T})>0, \qquad (2)$$

where:  $S_n$  islocal entropy of laminar flow;

 $S_{\pi}$  is averaged entropy of turbulent flow, allowing to consider transition from laminar flow to the turbulent one as a steady process of self-organization of flow modes of air-fuel mixtures in pneumatic conveying pipeline.

Mixtures' flow in a pipeline is accompanied by dissipation of energy for transportation and motion in largescale vortex formations within a single volume. In case of establishing asymptotically stable state of flow in the mainline pipeline, balance of external forces is equivalent to forces of the resistance to motion:

$$\sum F_{extern} = \sum F_{resist} .$$
 (3)

Dependence of energy of E mixture amount at steady motion on the ratio of external forces and forces of resistance to motion ( $\varepsilon_E$ ) and external energy force ( $\varepsilon_{EX}$ ) shows that at values close to  $\varepsilon_E \cong \varepsilon_{EX}$ , the system is in an unstable state.

In case of pneumatic transport, structures are easily ruined, passing in a stable state: transportation in flight mode of individual particles in suspensionor fluidized flow. Individual particles of flowing mixture volume have the properties required for transition into the intermitting mode. Presence of internal friction in the given system implies existence of an attractor, i.e., asymptotic limit  $(t \to \infty)$  of decisions, which is not directly affected by the initial condition – the starting point. Vibration motion of particles exists in limited, poorly overlapped intervals of the investigated parameter  $(\tilde{\Pi})$  values. Stochastic mode should be established at such a value of parameter  $(\tilde{\Pi})$  when it goes beyond  $[\tilde{\Pi}_1, \tilde{\Pi}_2]_2$  towards higher or lower values, for example:

$$\widetilde{\Pi}(t) = \frac{\widetilde{\Pi}_1 + \widetilde{\Pi}_2}{2} + (\widetilde{\Pi}_1 - \widetilde{\Pi}_2) \sin \varepsilon t$$
(4)

where:  $\varepsilon$  is a small parameter. *t* is time interval.

In this case, stochastic motion modes, both in pneumatic and hydraulic transport, arise while passing through intermittence, i.e. they are the result of collision of asymptotically stable and unstable motion states  $(\tilde{\Pi} = \tilde{\Pi}_1, \tilde{\Pi} = \tilde{\Pi}_2)$ . Another reason of transition is explained in the following way: there is always arbitrarily small perturbation of motion (Landau scenario) when an attractor with a large number of independent frequencies becomes a so-called "strange attractor", containing stochastic attracting trajectories:

$$-\Pi = \beta \overline{\Theta}^2 \ ; \ \overline{\Theta}^2 = \frac{-\Pi}{\beta}, \tag{5}$$

where:  $\beta$  is a numerical coefficient;

 $\Theta$  is motion velocity of particles.

Fig. 1 is a graph of dependence of energy of air-fuel mixture volume  $\overline{E}$  with steady state of motion onvalue  $\widetilde{\Pi}$ , where  $\widetilde{\Pi} = \frac{\Pi}{\beta}$ . Pecked lines show corresponding unstable states of motion. The graph can be divided into three areas. When  $\widetilde{\Pi} < \widetilde{\Pi}_1$  (area I), oscillatory motion of material particles takes place, without separation from the surface of the pipe;  $\widetilde{\Pi} > \widetilde{\Pi}_2$  (area III) – particles are in flight (transportation mode is in suspension);  $\widetilde{\Pi}_1 < \widetilde{\Pi} < \widetilde{\Pi}_2$  (area II) – particles are in an unstable state. In the latter case, particles execute conditionally periodic translational and rotational motions. The structure has a small margin of stability and is easily ruined, passing to state  $\widetilde{\Pi} < \widetilde{\Pi}_1$  or  $\widetilde{\Pi} > \widetilde{\Pi}_2$ .



Fig.1. Dependence of air-fuel mixture energy on the ratio of external forces and resistance forces

Area II analysis shows that individual particles of the volume of the flowing mixture have properties to transfer to the intermitting mode at slow change in parameter  $\tilde{\Pi}$ . Stochastic mode should be established at such a change of  $\tilde{\Pi}$  when this parameter goes beyond interval  $\left[\tilde{\Pi}_1, \tilde{\Pi}_2\right]$ , both to higher and lower values. This approach makes it possible to explain stochastization of motionof rather complicated such non-conservative dynamical systems with lots of variables as pneumatic conveying systems for transporting bulk materials.

Similar dependence of air-fuel mixture energy on the ratio of external forces and resistance forces can be createdincase of hydraulic transportation.

Flow of mixtures with inner waves and inner portions turbulent motions is considered as a process of selforganization with collective motions, determining the efficiency coefficients of transfer of momentum, force and mass of the moving material flow. The process of selforganization of mass transfer in pneumatic conveyingtransportis carried out by additional energy supply of the moving material flow. Energy supply is realized by carrying gas, vibration or combined actions of several factors. Shape and roughness of particles and walls of the pipeline, carrying flow turbulence, system entropy, oscillatory processes observed during movement of bulk materials in the transport pipeline also contribute to creation of additional vorticity of the flow.

Hydraulic fluids and coal water suspensions consist of two separate phases: water - continuous medium (continuum) and solid particles (discrete medium). Taken separately, each of these phases is characterized by its specific properties. The discrete solid phase is characterized by its mechanical parameters, grainsize composition, angles of repose and internal friction, etc. While mixing fluid continuous and solid discrete media, a new continuous medium is formed - a suspension, properties of which differ from its constituents taken separately. Each particle of the fine solid phase in the fluid medium gets a liquid shell on its surface, resulting in a dipole formation with positive and negative charges. Dipoles orientation in the mixture volume is determined by interaction between them. As a result of this interaction, a structure is formed, and the suspension can be considered as a continuous medium. Under exposure of the volume of such a mixture to force F at the initial moment, the solvate shells of the dipoles are deformed and the initial shear stress develops, which is the result of elastic deformation in this case.

Then a shift of separate layers of the hydraulic fluid occurs with developing plastic viscosity. Such a mechanism ofdeveloping viscoplastic properties is typical of mixtures containing small and practically homogeneous particles.

CWF includes fine particles, though heterogeneous in size and shape. As a result, some solid particles will not be completely covered by the solvate shell or will lose it. During deformation of volume of such a suspension,viscoplastic friction is added to purely mechanical friction of the particles that have lost or have not got solvate shells on their surfaces. Viscosity in such mixtures manifests itself as a cumulative effect of plastic viscosity caused by resistance to shear of individual layers of the suspension and resistance to friction of solid particles that do not have solvate shells. Thus, development of viscoplastic properties in the volume of suspension is determined by both physical (formation of dipoles) and mechanical (friction) natures. According to this model, development of viscoplastic friction, arising resistance can be associated with some effective (apparent) viscosity [1].

The latter one differs from the Bingham-Shvedov model by the fact that effective viscosity takes into account both structural and plastic properties of the deformable volume of the fluid (suspension).

The work makes an attempt to refine the rheological model of the state of Non-Newtonian fluids, in which viscosity is considered as a function of the shear stress. Such a class of liquids includes coal water fuel, which depending on the properties, concentration and size of the solid component fractions can develop the properties of Bingham plastic, pseudoplastic and even thixotropic liquid.

As for multiparameter models, including the model of a rheologically complex medium (CWF), such a model is taken that reflects the nature of the change in a solid body under dynamic deformation:

$$\sum_{i=0}^{m} p_i \frac{\partial^i \tau}{\partial t^i} = \sum_{i=0}^{n} q_i \frac{\partial^i \varepsilon}{\partial t^i},$$
(6)

where:  $p_i$  is pressure in the *i*-th section of the hydrotransport pipeline;

 $q_i$  is the deformation component.

In this case, an option is considered when the transportation velocity is constant in time (stationary mode of transportation). Then the equation for the multiparameter model is written as follows:

$$p_0 \tau + p_1 \dot{\tau} = q_0 \varepsilon + q_1 \dot{\varepsilon} + q_2 \ddot{\varepsilon} \tag{7}$$

Having limited by three parameters, the general equation of the rheological model of coal water fuel has been obtained:

$$e + ig = \frac{\left[\left(e_m s + ce_0\right)\left(s + c\right) + e_m t^2 + ict\left(e_m - e_0\right)\right]}{\left(s + c\right)^2 + t^2}, (8)$$

where: s + it, e + ig are complex numbers;

s, t and e, g are normal and shear components of stresses and deformations respectively;

 $e_m$  is the shear component at the boundary of the elastic region;

 $e_0$  is the boundary of the plastic region.

Thus, the shear stress, the shear velocity and viscosity of the water coal fuel are determined based on the formulas obtained, regardless of the type of liquids to which the researched system belongs.

The refined rheological model will be used as a basis for mathematical modelling of the flow of the coal water fuel in industrial hydrotransport systems, which will allow taking into account the rheological parameters of the CWF in solving the Navier-Stokes equations.

The flow of the coal water fuel in hydrotransport systems, as well as any other fluid, is described by the Navier-Stokes equations and the continuity equation, which, with respect to the motion conditions in pipes, transform into boundary layer equations.

The main problems solved by intensification of processes in the transport pipeline are the following: increasing productivity, reducing energy consumption, increasing service life of pipelines and ancillary equipment, excepting particles' degradation, improving sedimentation, expanding technological possibilities of application of pipeline transport.

Intensification of processes taking place in the mainline pipeline is carried out by impact on the moving mixture: additional airstreams, vibration, volume effect of these two factors (Figure 2.3.).



Fig. 2. Scheme for determining basic parameters of pipeline transport



Fig.3. Implementation scheme of intensification processes in pipeline transport

Modes of mixtures' flow and their phase transitions can be predicted and described using the concept of partial determinateness. Under the proposed approach, the observed process y(t) acts as a determined (predictable) process when  $|1-D| \ll 1$ , as a random (unpredictable) process when  $|D| \ll 1$  or a partially determined (partially predictable) process when  $0 < |1-D| \ll 1$ . In this case D is the correlation measure of the forecast quality introduced as normalized correlation function (correlation coefficient between observation and prediction):

$$D(\tau) = \frac{\langle y(t)z(t) \rangle}{\langle y^2(t) \rangle \langle z^2(t) \rangle^{0.5}}, \ t = t_0 + \tau, \qquad (9)$$

Time of determined behaviour depends on fluctuation impacts on noise measurement system and defects in the model that is presented in the form of the following dependence:

$$\tau_{\rm det} = F(v, f, \Delta M), \qquad (10)$$

Where:  $\Delta M$  is interpreted as inaccuracy of the model.

However, as in any physical system, during motion of gas-material flows in the pipeline transporthere are preserved unavoidable noises in the form of thermal processes, electrostatic forces, electromagnetic interference, interfacial effects, transformations of multicomponent media. These unavoidable fluctuation effects define limits of predictability. If  $\nu \rightarrow 0$  and  $\Delta M \rightarrow 0$ , then the limit value (predictability horizon) is:

$$\tau_{\rm lim} = \lim \tau_{\rm det} = F(0, f, 0),$$
 (11)

Predictability horizon  $\tau_{\rm lim}$  characterizes time of dynamic system memory. At the same time, value  $\tau_{\rm lim}$  characterizes time of reversible behaviour and is comparable to the information storage time during which the observed process loses information about noises effectingthe system before. The concept of partial determinateness (randomness and determinism are not opposed to each other, but considered as single property (partial determinism) poles) can be used in description of turbulent flows, as they have compatibility spatial domain [25].

### CONCLUSIONS

The analysis showed that further development and improvement of pipeline transport should be based on modern methodological approaches, based on the synergetic concept.

Analysis of the processes occurring in the pneumatic conveying transport during transportation of bulk materials showed that:

- transportation of bulk materials in transport pipeline under the influence of the carrying air flow may be regarded as an open system with inherent characteristics;

- adoption of postulates of synergy suggests that constantly occurring non-equilibrium phase transitions in pneumatic conveying transport take place according to the scheme  $O \leftrightarrow C$  (order - chaos), i.e. under the scheme of self-organization;

- stochastic motion modes arise while passing through intermittence, i.e. they are the result of collision of asymptotically stable and unstable motions of air-fuel mixtures' flow;

- flow of air-fuel mixture with inner weaves and inner portion turbulent motions is considered as a process of

self-organization with collective movements, determining effective coefficients of transfer of momentum, force and mass of the moving material flow. Explanation of the phenomena, taking place in transport pipeline during flow of mixtures in non-stationary modes of mass transfer under non-traditional version of material pipeline allows identifying and implementing a number of new technical solutions aimed at improving the transport pipeline.

#### REFERENCES

1. **Loitsiansky, L.G. 1986.** Fluid and Gas Mechanics [Text] / L.G. Loitsiansky. – M.: Nauka, 737. (in Russian)

2. **Smoldyrev, A.E. 1980.** Pipeline Transport / A.E. Smoldyrev. – M.: Nedra, 293. (in Russian).

3. **Smoldyrev, A.E. 1985.** Hydraulic and Pneumatic Transport in Metallurgy / A.E. Smoldyrev. – M.: Metallurgy, 80. (in Russian).

4. **Nigmatulin, R.I. 1987.** Dynamics of Multiphase Media/ R.I.Nigmatulin. –M.: Nauka, 464. (in Russian).

5. Voloshin, A.I. 2001. Mechanics of Pneumatic Transportation of Solids / A.I.Voloshin, B.V. Ponomarev. – K.: NaukovaDumka, 519. (in Russian).

6. **Poturaev, V.N. 1989.** Vibration and Pneumatic Equipment for Bulk Materials / V.N.Poturaev, A.I.Voloshin, B.V.Ponomarev. – K.: NaukovaDumka, 248. (in Russian).

7. **Razumov, I.M. 1984.** Fluidization and Pneumatic Transport of Bulk Materials / I.M. Razumov. – M.: Khimiia, 346. (in Russian).

8. **Ostrovsky, G.M. 2000.** Applied Mechanics of Inhomogeneous Media / G.M. Ostrovsky. –SPb.: Nauka, 359. (in Russian).

9. Sow, S. 1971. Hydrodynamics of Multiphase Systems / S. Sow. – M.: Mir, 536. (in Russian).

10. Michaelides, E.E. 1988. Average Velocity and Pressure Loss / E.E.Michaelides // Journal of Basic Engineering. Proceedings of the American Society of Mechanical Engineers. - №1, 276-288. (in Russian).

11. Choi, Y.D. 1983. Investigation of Turbulent Flow in Gas Pipe with Suspended Solids / Y.D. Choi // Journal of Basic Engineering. Proceedings of the American Society of Mechanical Engineers. –  $N_{23.166-172.}$  (in Russian).

12. **Traynis, V.V. 1970.** Parameters and Modes of Hydraulic Transportation of Coal via Pipelines: scientific edition / V.V.Traynis; The USSR Academy of Sciences. – M.: Nauka, 192. (in Russian).

13. N. Chernetskaya-Beletskaya, A. Kushchenko, E. Varakuta, A. Shvornikova, D. Kapustin. 2014. Define the operational hydro-solid waste handling system. TEKA. Commission of motorization and energetics in agriculture, Vol. 14, No.1, 10-17.

14. N. Chernetskaya-Beletskaya, A. Kuschenko, D. Kapustin. 2012. Experimental research of hydrotransporting concentrated residues at solid fuel burning. TEKA. Commission of motorization and energetics in agriculture, Vol. 12, No.4, 19-22.

15. N. Chernetskaya-Beletskaya, I. Baranov, M. Miroshnykova. 2015. Technology of breakage of coal for the coal-water fuel production. TEKA. Commission of motorization and energetics in agriculture, Vol. 15, No.2, 63-68.

16. **Murko, V.I. 1999.** Scientific bases of processes reception and effective use coal-water suspensions: Dis. on competition degree of Dr.tehn. Sciences. Novokuznetsk, 289.

17. **Gushchin, V.M. 2010.** Analysis of Driving Modes of Air-Fuel Mixture in Pneumatic Conveying Transport / V.M., Gushchin, O.V.Gushchin // Visnyk-Donbaskoyiderzhavnoymashinobudivnoiakademiyi: thematic collection of scientific works. –Kramatorsk: DDMA, №1. (in Russian).

18. **Gushchin,V.M. 2000.** New Concept and Its Implementation in Development of Highly Efficient Ways of Pneumatic Transportation of Bulk Materials / V.M. Gushchin // Mashinoznavstvo. №2 (23). 39-43. (in Ukrainian).

19. **Gushchin, V.M. 2009.** Management and Intensification of Processes of Pneumatic Transportation of Bulk Materials by Stream Influence of Airflow / V.M.Gushchin, O.V.Gushchin // TeoriyaiPraktykaBudivnytstva, №5, 6-15.

20. **O. Guschin, N. Cherneckaya-Veleckaya. 2015.** Synergies in the motion processes of the structured aeromixtures in a pneumatic transport pipeline. TEKA. Commission of motorization and energetics in agriculture, Vol. 15, No.3, 21-28.

21. **Haken, H. 1991.** Information and Self-Organization: A Macroscopic Approach to Complex Systems / H. Haken // Trans. from English. – M.: 204. (in Russian).

22. Klimontovich, Y.L. 1990. Turbulent Flow and Structure of Chaos. A New Approach to Statistical Theory of Open Systems / Y.L. Klimontovich // M.: Nauka, 320. (in Russian).

23. **Berge, P. 1991.** Order within Chaos. Towards a Deterministic Approach to Turbulence: Trans. from France. / P. Berge, I. Pomo, K. Vidal // M.: Mir, 368. (in Russian).

24. Gushchin, O.V., Chernetskaya-Beletskaya, N.B. 2015. Improving Pneumatic Transportation of Bulk Materials on the Basis of Synergetic Concept. Visnyk-SkhidnoukrainskogonatsionalnogouniversytetuimeniVolodymyra Dalia№ (218) Severodonetsk, 12-16. (in Russian).

25. **Kravtsov, Y.A. 1989.** Randomness, Determinism and Predictability / Y.A. Kravtsov // UFN. P. 158. 93-122. (in Russian).

## НЕКОТОРЫЕ АСПЕКТЫ СОВЕРШЕНСТВОВАНИЯ ПРОМЫШЛЕННОГО ТРУБОПРОВОДНОГО ТРАНСПОРТА

Чернецкая-Белецкая Н.Б., Баранов И.О., Мирошникова М.В., Кравченко С.В., Брагин М.И.

Аннотация. Совершенствование и разработка новых высокоэффективных энергосберегающих способов трубопроводного транспорта предлагается осуществить на базе современных научных подходов. Предложена новая концепция и ее реализация на синергетической основе. Показано, что стохастические режимы движения смесей, возникают при переходе через перемеживаемость, т.е. являются следствием столкновения асимптотически устойчивых и неустойчивых состояний движения. Представленный график зависимости энергии объема смеси от показателя П, отражающего меру неустойчивости. На этом графике выделено 3 области: в области I имеет место колебательное движение частиц сыпучего материала без отрыва от поверхности трубы; область II – частицы находятся в неустойчивом состоя-

нии; область III - частицы находятся во взвешенном состоянии (режим транспортирования частиц в поле-

те). Анализ области II показывает, что отдельные частицы объема перемещающейся смеси обладают свойствами для перехода в перемеживающийся режим при медленном изменении параметра П.

Ключевые слова: трубопроводный транспорт, сыпучий материал, синергетика, перемеживаемость, энергосбережение.